



HEVEA MATS

HeveaMats ApS
Adresse: Tirslundvej 34, 6650 Brørup
Tlf: +45 61669044
Email: info@HeveaMats.dk
Web: www.HeveaMats.dk

Datablad JVD 1

Dansk

| | |
|------------|---|
| Anvendelse | Gangstier, haven, terrassen, altanen osv. |
|------------|---|

| | |
|-------|-----------------------------|
| Fiber | Polyethylen og polypropylen |
|-------|-----------------------------|

| | |
|-------------------|---|
| Produktionsmetode | Tufted - 3/8" |
| Primær baggrund | 100% Polypropylen sort, UV-stabiliseret |
| Sekundær baggrund | SBR-gummi |
| Strå | 13.650 /m ² (+/- 10%) |
| Højde strå | 22 mm. (+/- 10%) |
| Total højde strå | 24 mm. (+/- 10%) |
| Strå vægt | 625 g/m ² (+/- 10%) |
| Total vægt | 1.410 g/m ² (+/- 10%) |

| | |
|------|--|
| Fyld | Sand (> 80% rund), 2-5 kg/m ² |
|------|--|

| | |
|--------------|-----------------------|
| Rulle bredde | 200 cm eller 400 cm |
| Rulle længde | I henhold til lay-out |

| | |
|-------|------|
| Farve | Grøn |
|-------|------|

| | |
|-------------------|------------------------------|
| UV-stabilitet | > 6000 timer |
| Vandpermeabilitet | 60 liter/min/ m ² |

Engelsk

| | |
|------------|--|
| Employment | Walkways, garden, terrace, balcony, etc. |
|------------|--|

| | |
|-------|--------------------------------|
| Fibre | Polyethylene and Polypropylene |
|-------|--------------------------------|

| | |
|-------------------|-------------------------------------|
| Production method | Tufted - 3/8" |
| Primary backing | 100 % PP black, UV-stabilized |
| Secondary backing | SBR Latex |
| Stitches | 13.650 /m ² (+/- 10%) |
| Pile height | 22 mm. (+/- 10%) |
| Total height | 24 mm. (+/- 10%) |
| Pile weight | 625 gr / m ² (+/- 10%) |
| Total weight | 1.410 gr / m ² (+/- 10%) |

| | |
|--------|---|
| Infill | Sand (> 80% round), 2-5 kg/m ² |
|--------|---|

| | |
|-------------|----------------|
| Roll Width | 200 or 400 cm |
| Roll Length | As per lay-out |

| | |
|--------|-------|
| Colour | Green |
|--------|-------|

| | |
|--------------------|------------------------------|
| UV-Stability | > 6.000 hours |
| Water Permeability | 60 liter/min/ m ² |